



COLORED AND VERSATILE

Totally matching every type of decorative solution thanks to the possible customizations



COMPLETE RANGE

Available versions: COMPETITION, SED and SAP 1, 2, 3 groups, "Tall" and "Compact"



SHOT TIMER

To accurately and reliably time coffee extraction (only COMPETITION)



Version with shot timer and barista lights



It guarantees an electronic dosing system through the button panel



It allows the semi-automatic programming of doses



EASY SERVICE

Easy access to the internal parts for a quick and simple technical assistance

LOW SERVICE COST


Designed to decrease the maintenance and inspection costs




SANREMO

COFFEEMACHINES


Models




20.87 inches / 530 mm



28.35 inches / 720 mm



37.40 inches / 950 mm



20.87 inches / 530 mm

21.14 inches / 537 mm

21.38 inches / 543 mm

1 group COMPETITION-SED-SAP

- 1 steam tap
- 1 water tap
- 1 one-cup portafilters
- 1 two-cup portafilters

2 group COMPETITION-SED-SAP

- 2 steam taps
- 1 water tap
- 1 one-cup portafilters
- 2 two-cup portafilters

3 group COMPETITION-SED-SAP

- 2 steam taps
- 1 water tap
- 1 one-cup portafilters
- 3 two-cup portafilters


2 group COMPACT

- 2 steam taps
- 1 water tap
- 1 one-cup portafilters
- 2 two-cup portafilters




TALL VERSION

1-2-3 groups COMPETITION-SED-SAP



20.78 inches / 528 mm



5.51 inches / 140 mm

23.7 inches / 602 mm

Characteristics



ELECTRONIC AUTO-LEVEL
Through an electronic level probe the boiler is automatically filled and maintained at the right level.



EASY SERVICE
Easy access to the internal parts for a quick and easy technical assistance.



ACTIVATED ELECTRONIC PRE-INFUSION
Management of the delayed activation of solenoid in the first phase of brewing.



AUTOMATIC CLEANING CYCLE
Process to clean the coffee groups.



DOUBLE READING GAUGE
It allows to control at the same time the boiler pressure and the brewing pressure.



LED LIGHT OF THE WORKING AREA
It allows to effectively work in any lighting condition. (only COMPETITION)

Optional



AUTOSTEAM
Steam pipe characterized by an electronic system that allows to froth and or heat milk at the set temperature.



CUP HEATER
Dedicated resistor to keep all the cups at the optimal temperature.



EXTERNAL VOLUMETRIC PUMP



BLUETOOTH COMMUNICATION SYSTEM



NAKED PORTAFILTERS

Technical data

	1 group	2 group	3 group	compact	
voltage	V	220-240 1N	280-415 3N		
power input	kW	2.3	3.3	6	2.7
steam boiler capacity	US gal / lt	1.19 / 4.5	2.64 / 10	3.7 / 14	1.85 / 7
steam boiler power	kW	2.15	2.95	5.6	2.5
pump power	kW	0.13	0.13	0.13	0.13
net weight	lb / kg	90 / 41	121 / 55	152 / 69	99 / 45

Colors

	Black	RAL 9005
	White/Black	RAL 9003/9005
	White/Matte black	RAL 9003/9005
	White/Red	RAL 9003/3002



Zoe
Link to the website

Customization of internal panels with graphics and colors (on request).

